

Safetron 5150



Tootekirjeldus

- Certified according to SSF-3522: lock class 2A
 - Certified according to SS-EN 14846: Security Grade 5
 - Back set 50 mm
 - Straight-line piston
 - Adapted for automatic door openers
 - Built-in sensors: rule in, rule out, door status (magnetic contact).
 - Disengagement: 0.3 seconds
 - Openable with key/knob
 - Plug and play installation
-
- Voltage: 10-35 VDC / 8-24 VAC
 - Power consumption: 50 mA, max 350 mA
 - Working temperature -20°C to +40°C
 - Suitable for Scandinavian oval and round cylinders

TOOTENIMETUS	SOODUS	HIND
Safetron 5150 D¼D¼Ñ,D¼Ñ€D½Ñ<D¹ D·D°D¼D¾D°		992.53 €
Safetron 5150 D¼D¼Ñ,D¼Ñ€D½Ñ<D¹ D·D°D¼D¾D° + oÑ,D²DµÑ,D½Ñ<Dµ D¿D»D°D½D°D, + D¿Ñ€D¾D²D¾D´ + D°D°D±DµD»DµD¿Ñ€D¾Ñ D¾D´Ñ< + ÑfÑ•Ñ,Ñ€D¾D¹Ñ•Ñ,D²D¾ ÑfD¿Ñ€D°D²D»DµD½D,Ñ•		1683.91 €

