

Safetron 6300



Tootekirjeldus

- Certified according to. SSF 3522: lock class 2B, 3, 4 and 5.
 - Certified according to. SS-EN 14846: Security Grade 7
 - Back set 35 mm
 - Hook rule
 - Adapted for automatic door openers
 - Built-in sensors: rule in, rule out, door status (magnetic contact).
 - OSDP® via RS-485
 - 128-bit AES encryption
 - Disengagement: 0.1 seconds
 - Openable with key/knob (90 degree turn)
 - Plug and play installation
 - Up to 100m cable between motor lock and controller
 - Event log
 - Service module in control unit
 - Series connection, up to two motor locks to one controller
 - The product has been assessed by [Byggvarubedomningen](#)
-
- 10-48VDC
 - Power consumption:

Motor lock 6300

12VDC: Rest: 20mA / Max: 200mA

24VDC: Rest 10mA / Max: 100mA

Motor lock 6300 + Controller CU2

12VDC: Rest: 120mA / Max: 300mA

24VDC: Rest 60mA / Max: 150mA

- Working temperature -30°C to +70°C
- Suitable for Scandinavian oval and round cylinders

TOOTENIMETUS	SOODUS	HIND
Motor lock Safetron 6300		603.90 €
Motor lock Safetron 6300 + striker plate + cable + lead cover		1674.47 €
Motor lock Safetron 6300 + striker plate + cable + lead cover + control unit		2211.86 €



