

ABLOY PRESTO 3-20/0650 EXIT



Tootekirjeldus

A pair of links with a split spindle, for escape route doors.

Complies with evacuation standard EN179.

Features:

- Shield: Abloy 0650
- Standard delivery for doors with a thickness of 38-54 mm
- Includes 2 return springs
- The reinforced spring ensures durability even on heavy and frequently used doors
- Suitable for aluminum and steel profiles with Finnish standard key sockets
- Split spindle

Material: aluminum

Surface finishes:

- Cr (chromium)
- Aho (anodized aluminum)
- Val (white, powder coated RAL 9010)
- Mus (black, powder coated RAL 9005)
- Gra (graphite, powder coated RAL 790-M)
- Har (grey, powder-coated RAL 9006)

TOOTENIMETUS	SOODUS	HIND
Đ ÑƒÑ‡Đ°Đ° Đ'Đ»Ñ• Đ°Đ²Đ°Ñ€Đ,Đ¹Đ½Đ¾Đ³Đ¾ Đ²Ñ‹Ñ Đ¾Đ'Đ° ABLOY PRESTO 3-20/0650 EXIT Al/CR (Đ±Đ»ĐµÑ•Ñ,Ñ•Ñ%Đ,Đ¹ Ñ Ñ€Đ¾Đ¼, Đ'Đ»Ñ• Đ¿Ñ€Đ¾Ñ,,Đ,Đ»Ñ€Đ½Ñ‹Ñ Đ'Đ²ĐµÑ€ĐµĐ¹ 38-54 Đ¼Đ¼, Ñ€Đ°Đ·Đ'ĐµĐ»ĐµĐ½Đ½Ñ‹Đ¹ ÑˆĐ¿Đ,Đ½Đ'ĐµĐ»Ñ€)		102.35 €
Đ ÑƒÑ‡Đ°Đ° Đ'Đ»Ñ• Đ°Đ²Đ°Ñ€Đ,Đ¹Đ½Đ¾Đ³Đ¾ Đ²Ñ‹Ñ Đ¾Đ'Đ° ABLOY PRESTO 3-20/0650 EXIT Al/AHO (Đ°Đ½Đ¾Đ'Đ,Ñ€Đ¾Đ²Đ°Đ½Đ½Ñ‹Đ¹ Đ°Đ»ÑŽĐ¼Đ,Đ½Đ,Đ¹, Đ'Đ»Ñ• Đ¿Ñ€Đ¾Ñ,,Đ,Đ»Ñ€Đ½Ñ‹Ñ Đ'Đ²ĐµÑ€ĐµĐ¹ 38-54 Đ¼Đ¼, Ñ€Đ°Đ·Đ'ĐµĐ»ĐµĐ½Đ½Ñ‹Đ¹ ÑˆĐ¿Đ,Đ½Đ'ĐµĐ»Ñ€)		89.69 €
Đ ÑƒÑ‡Đ°Đ° Đ'Đ»Ñ• Đ°Đ²Đ°Ñ€Đ,Đ¹Đ½Đ¾Đ³Đ¾ Đ²Ñ‹Ñ Đ¾Đ'Đ° ABLOY PRESTO 3-20/0650 EXIT Al/VAL (Đ±ĐµĐ»Ñ‹Đ¹ RAL 9010, Đ'Đ»Ñ• Đ¿Ñ€Đ¾Ñ,,Đ,Đ»Ñ€Đ½Ñ‹Ñ Đ'Đ²ĐµÑ€ĐµĐ¹ 38-54 Đ¼Đ¼, Ñ€Đ°Đ·Đ'ĐµĐ»ĐµĐ½Đ½Ñ‹Đ¹ ÑˆĐ¿Đ,Đ½Đ'ĐµĐ»Ñ€)		102.29 €
Đ ÑƒÑ‡Đ°Đ° Đ'Đ»Ñ• Đ°Đ²Đ°Ñ€Đ,Đ¹Đ½Đ¾Đ³Đ¾ Đ²Ñ‹Ñ Đ¾Đ'Đ° ABLOY PRESTO 3-20/0650 EXIT Al/MU (Ñ‡Ñ•Ñ€Đ½Ñ‹Đ¹ RAL 9005, Đ'Đ»Ñ• Đ¿Ñ€Đ¾Ñ,,Đ,Đ»Ñ€Đ½Ñ‹Ñ Đ'Đ²ĐµÑ€ĐµĐ¹ 38-54 Đ¼Đ¼, Ñ€Đ°Đ·Đ'ĐµĐ»ĐµĐ½Đ½Ñ‹Đ¹ ÑˆĐ¿Đ,Đ½Đ'ĐµĐ»Ñ€)		102.29 €
Đ ÑƒÑ‡Đ°Đ° Đ'Đ»Ñ• Đ°Đ²Đ°Ñ€Đ,Đ¹Đ½Đ¾Đ³Đ¾ Đ²Ñ‹Ñ Đ¾Đ'Đ° ABLOY PRESTO 3-20/0650 EXIT Al/HAR (Ñ•ĐµÑ€Ñ‹Đ¹ RAL 9006, Đ'Đ»Ñ• Đ¿Ñ€Đ¾Ñ,,Đ,Đ»Ñ€Đ½Ñ‹Ñ Đ'Đ²ĐµÑ€ĐµĐ¹ 38-54 Đ¼Đ¼, Ñ€Đ°Đ·Đ'ĐµĐ»ĐµĐ½Đ½Ñ‹Đ¹ ÑˆĐ¿Đ,Đ½Đ'ĐµĐ»Ñ€)		102.30 €
Đ ÑƒÑ‡Đ°Đ° Đ'Đ»Ñ• Đ°Đ²Đ°Ñ€Đ,Đ¹Đ½Đ¾Đ³Đ¾ Đ²Ñ‹Ñ Đ¾Đ'Đ° ABLOY PRESTO 3-20/0650 EXIT Al/GRA (Đ³Ñ€Đ°Ñ,,Đ,Ñ,Đ¾Đ²Ñ‹Đ¹ RAL 790-M, Đ'Đ»Ñ• Đ¿Ñ€Đ¾Ñ,,Đ,Đ»Ñ€Đ½Ñ‹Ñ Đ'Đ²ĐµÑ€ĐµĐ¹ 38-54 Đ¼Đ¼, Ñ€Đ°Đ·Đ'ĐµĐ»ĐµĐ½Đ½Ñ‹Đ¹ ÑˆĐ¿Đ,Đ½Đ'ĐµĐ»Ñ€)		102.29 €