

Abloy EL560



Tootekirjeldus

Features:

- Voltage: 12-24 VDC
- Backset: 55 / 65 / 100 mm
- Operating temperature range: -20°C kuni +60°C
- Faceplate: 24 mm
- Recommended to be used in interior doors of business premises, public buildings, hospitals, educational premises etc.
- Only outside handle is electrically controlled. The lock can always be opened by inside handle. Mechanical opening by cylinder is always possible

TOOTENIMETUS	SOODUS	HIND
D_iD^{3/4}D»D_μD^{1/2}D^{3/4}D₃D^{1/2}N̄D¹D·D°D^{1/4}D^{3/4}D° Abloy EL560/100 (N̄· N̄E°D·N̄ŠD_μD^{1/4}D^{1/2}N̄D^{1/4}D²D°D»D^{3/4}D^{1/4}, N̄·D₃D^{1/4}D^{1/4}D_μN̄,N̄E°D,N̄‡D^{1/2}D°N̄· D_εD_μN̄E°D_μD^{1/2}N̄·N̄·D_εD»D°N̄·N̄,D₃D^{1/2}D°)		727.57 €
D_iD^{3/4}D»D_μD^{1/2}D^{3/4}D₃D^{1/2}N̄D¹D·D°D^{1/4}D^{3/4}D° Abloy EL560/55 (N̄· N̄E°D·N̄ŠD_μD^{1/4}D^{1/2}N̄D^{1/4}D²D°D»D^{3/4}D^{1/4}, N̄·D₃D^{1/4}D^{1/4}D_μN̄,N̄E°D,N̄‡D^{1/2}D°N̄· D_εD_μN̄E°D_μD^{1/2}N̄·N̄·D_εD»D°N̄·N̄,D₃D^{1/2}D°)		727.57 €
D_iD^{3/4}D»D_μD^{1/2}D^{3/4}D₃D^{1/2}N̄D¹D·D°D^{1/4}D^{3/4}D° Abloy EL560/65 (N̄· N̄E°D·N̄ŠD_μD^{1/4}D^{1/2}N̄D^{1/4}D²D°D»D^{3/4}D^{1/4}, N̄·D₃D^{1/4}D^{1/4}D_μN̄,N̄E°D,N̄‡D^{1/2}D°N̄· D_εD_μN̄E°D_μD^{1/2}N̄·N̄·D_εD»D°N̄·N̄,D₃D^{1/2}D°)		727.58 €

