

Safetron SL620



Tootekirjeldus

- Adjustable latch bolt placement between ASSA connect and classic
- Split function, mechanical inside lever handle
- Simple function, electric activation both sides
- Easily adjusted between right or left
- Fire rating: 120 min [E/EI 120]
- Back set 50 mm
- emergency exit according to EN 179:2008 with Emergency device 793 & 794
- Approved with type T emergency opener by Söderhamn innovation
- Fail secure function: SL620
- Fail safe function: SL621
- Handle movement indication
- Locked indication
- Door status indication when using magnet in strike plate
- Knob/cylinder indication
- Latch bolt length: 14 mm
- Voltage: 12-24 VDC (-10%/+15%)

Power consumption:

- 12 VDC: 70mA, 0mA at rest
- 24 VDC: 40mA, 0mA at rest

- Working temperature -20°C to +40°C

TOOTENIMETUS	SOODUS	HIND
Diagnostika- ja mõõtmisvahend, mis võimaldab kiiresti ja lihtsalt tuvastada ja kõrvaldada voolu- ja pingetõrkeid, mis põhjustavad masinate ja seadmete töökatkestusi. Safetron SL620		603.90 €
Diagnostika- ja mõõtmisvahend, mis võimaldab kiiresti ja lihtsalt tuvastada ja kõrvaldada voolu- ja pingetõrkeid, mis põhjustavad masinate ja seadmete töökatkestusi. Safetron SL620 + diagnostika- ja mõõtmisvahend, mis võimaldab kiiresti ja lihtsalt tuvastada ja kõrvaldada voolu- ja pingetõrkeid, mis põhjustavad masinate ja seadmete töökatkestusi.		701.32 €



